

50-R Rust Inhibitor



An economical, aqueous based, interim process rust inhibitor for ferrous metals. Other notable product features include:

- Provides a highly effective, invisible, non-sticky, non-greasy barrier.
- Will not affect color of part.
- This product does not contain any ingredients that are subject to rancidity.
- Will not interfere with subsequent operations such as painting, soldering, brazing, welding, anodizing or electroplating.

PHYSICAL PROPERTIES

Appearance	Blue liquid
pH @ 1% solution	10.2
Odor	Mild
Foaming Action	Very low
Solubility in water	Complete
Rinsing Action	Excellent
Metal Safety	Ferrous & Non-ferrous
Flash Point	None
Stability	Stable
Standard Container	55 gal drum

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 60 years experience. Our quality management system has been certified to ISO 9001 quality standards.

USAGE AND DILUTION RECOMMENDATIONS

Where severe rusting conditions are likely to occur, use 6 ounces of 50-R per gallon of water. For less severe conditions, use 3 ounces of 50-R per gallon. Solutions should be applied in final stage of parts washer by spray or soak application. Solution temperature can vary from room temperature to 170° F. for steel parts and 60° to 80° for cast iron or sintered metal parts. Solutions which are properly maintained in accordance to manufacturer's recommendations will give a minimum of 2-3 weeks protection if packed wet, 60 to 90 days protection if packed dry. Parts exposed to excessively high humidity, rain, mists, water or salt spray, acid fumes or harsh environments will have reduced protection periods. May be used in hot or cold solutions, however, when inhibiting cast iron or sintered metals, it is strongly recommended that ambient or cold water be used.

HANDLING AND STORAGE

This product poses no fire hazards. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, and an impermeable apron and other appropriate protective clothing as necessary. If eye contact occurs, flush with plenty of water for at least 15 minutes and consult physician. In case of skin contact, wash with soap and water, removing contaminated clothing and shoes. Store product in a tightly closed container between 45° and 85° F. Rotate stock. When stored as stated above, shelf life is a minimum of 2 years.

Refer to our Safety Data Sheet for additional information.